



SC5b-9 PLUS ENZYME IMMUNOASSAY KIT (COMPLEMENT ASSAY KIT)



Catalog No.: A020 / A029

Reference No.: N/A

Revision Date: March 19, 2007

SECTION 1 – Kit / Preparation and Company Identification

1.1 SC5b-9 PLUS ENZYME IMMUNOASSAY KIT

(For Research Use Only within the U.S. – Not for use in Diagnostic procedures)

1.2 An enzyme immunoassay for the quantitation of the SC5b-9 complex present in human plasma or serum.

1.3 **Manufacturer:** Quidel Corporation – 10165 McKellar Court – San Diego, CA 92121

Telephone No.: 1-858-552-1100 **Toll Free No.:** 1-800-874-1517 **Fax No.:** 1-858-453-4338

1.4 **Emergency No.:** Poison Control @ 1-800-876-4766 (USA only)

SECTION 2 – Composition / Ingredients Information

2.1 **Description of Components:** Coated strips, SC5b-9 Standards, Stop Solution, 20x Wash Solution Concentrate, Complement Specimen Diluent, TMB+ Substrate Chromogen¹, SC5b-9 Plus Conjugate, High/Low Controls

2.2 **Hazardous Ingredients:** Dangerous solid or liquid substances present in >1% (or as required by applicable U.S., Canadian and E.U. regulations):

CAS#	EINECS	Chemical Name	Kit Component	% Weight	Classification:			
					US OSHA	WHMIS	EU	Risk Phrases
7664-93-9	231-639-5	Sulfuric Acid	Stop Solution (4978)	<10.0	Corrosive	E	Xi	R: 36/38

**See Section 15 and Section 16 – Regulatory Information for additional information on hazard classifications.

SECTION 3 – Hazard Identification

Emergency Overview: As part of good industrial and personal hygiene and safety procedure, avoid all unnecessary exposure to the chemical components within this kit and ensure prompt removal from skin, eyes, and clothing.

3.1 Some components of this kit are considered as hazardous or dangerous preparations as defined by the Occupational Safety and Health Administration (OSHA), the Canadian Workplace Materials Information System (WHMIS), and/or the European Union (EU) Directives 1999/45/EC and 67/548/EEC. **No significant health effects are anticipated from routine use of this kit when following the precautions listed below.**

3.2 Contact with **Stop Solution #4978** to the eyes and/or skin may cause irritation upon a single exposure or prolonged exposure. Avoid inhalation of sulfuric acid mist.

3.3 This kit contains material of human and/or animal origin and should be considered as potentially capable of transmitting infectious diseases.

3.4 All patient samples, contaminated plates, and fluids should be handled as potentially infectious. Follow **Universal Precautions** as necessary.

¹ TMB+ Substrate Chromogen is provided by Dako Cytomation – 6392 Via Real – Carpinteria, CA 93013 (805) 566-6655

3.5 Warning Properties:

Chemical Name	Kit Component	Degree	Description
Sulfuric Acid	4978	Poor	Colorless, Odorless

SECTION 4 – First Aid Measures


Special Instructions:

- 4.1 **Inhalation** Inhalation of any component in this kit is unlikely. However, if a component of this kit is inhaled and causes discomfort, move exposed individual to fresh air. Seek medical attention if breathing is difficult or symptoms persist.
- 4.2 **Eye Contact** Component #4978 – sulfuric acid, may cause irritation upon contact. If this component enters the eyes, immediately flush eyes under potable running water for 15 minutes or longer, making sure that the eyelids are held open. If other components of this kit enter the eyes and cause discomfort, gently wash eyes under potable running water for 15 minutes or longer, making sure that the eyelids are held open. For both situations, if pain or irritation occurs, obtain medical attention.
- 4.3 **Skin Contact** Component #4978 – sulfuric acid, may cause irritation upon contact. If this component contacts the skin, remove any contaminated clothing and wash affected area with plenty of water. Excess acid on skin can be neutralized with 2% solution of bicarbonate of soda. If other components of this kit contact the skin and causes discomfort, remove any contaminated clothing. Wash affected area with plenty of soap and water. For both situations, if pain or irritation occurs, obtain medical attention.
- 4.4 **Ingestion** If a component of this kit is ingested, wash mouth out with water. If irritation or discomfort occurs, obtain medical attention. Do NOT induce vomiting unless directed to do so by medical personnel.

SECTION 5 – Fire Fighting Measures

- 5.1 **Extinguishing Media:** For small fires, use dry chemical, carbon dioxide, or alcohol-resistant foam.
- 5.2 **Special Fire Fighting Procedures:** This material will not significantly contribute to the intensity of a fire. Use extinguishing material suitable to the surrounding fire. Utilize proper personal protective equipment when responding to any fire. Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Move containers from fire area if it can be done without risk to personnel. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.
- 5.3 **Unusual Fire and Explosion Hazards:** When involved in a fire, this material can decompose and produce irritating fumes and toxic gases (e.g., Carbon monoxide, Carbon dioxide).
 - Explosion Sensitivity to Mechanical Impact: Not sensitive under normal conditions.
 - Explosion Sensitivity to Static Discharge: Not sensitive under normal conditions.
- 5.4 **Additional Considerations (Stop Solution #4978):**
 - 5.4.1 Flash Point Non Combustible
 - 5.4.2 Auto-ignition Temperature Not Determined
 - 5.4.3 Upper / Lower Explosion Limit Not Determined

5.5 NFPA Ratings (see Section 16 for definitions of numerical ratings):



***Only trained and competent personnel shall attempt to extinguish a fire. Contact emergency response personnel as required. Be cautious of surrounding materials that may react with the extinguishing media.*

SECTION 6 – Accidental Release Measures

- 6.1 Personal Precautions:** This kit contains materials of biological origin. Avoid personal contact. Use Universal Precautions during clean-up procedures.
- 6.2 Environmental Precautions:** No environmental hazard is anticipated provided that the material is handled and disposed of with due care. Contain spill to prevent migration.
- 6.3 Spill and Leak Procedures:** Large spills of this kit are unlikely. Personnel who have received basic chemical safety training can generally handle small-scale releases, such as one container within this kit. For Stop Solution #4978, neutralize the residue with a dilute solution of sodium carbonate (as necessary). Utilize safety glasses, nitrile gloves, and lab coat/apron when responding to spills involving the components of this kit. Absorb liquid and place in container suitable for disposal. Dispose of in accordance with applicable U.S. Federal, State, or local procedures or appropriate standards of Canada or the EU (see Section 13, Disposal Considerations).

SECTION 7 – Handling and Storage

- 7.1 Handling:** As with all chemicals, avoid getting components within this kit ON YOU or IN YOU. Wash exposed areas thoroughly after using this kit. Do not eat or drink while using this kit. This kit should be handled only by qualified clinical or laboratory employees trained on the use of this kit and who are familiar with the potential hazards. This kit should be handled as though capable of transmitting infectious diseases. Universal Precautions should be followed when using this kit. **Not for use by the general public.**
- 7.2 Storage:** Keep away from incompatible materials (Section 10). To maintain efficacy, store according to the package insert instructions.
- 7.3 Specific Use:** **For research use only within the U.S. – Not for use in diagnostic procedures!**

SECTION 8 – Exposure Controls and Personal Protection

8.1 Exposure Limits:

CAS#	Chemical Name	OSHA (PEL)	ACGIH (TLV)	MAK
7664-93-9	Sulfuric Acid	1.0 mg/m ³	1.0 mg/m ³	1.0 mg/m ³

8.2 Occupational Exposure Controls:

8.2.1 Engineering Controls:

No special engineering controls are required when working with this kit. Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above.

8.2.2 Personal Protective Equipment (PPE):

Respiratory Protection:

None needed under normal conditions of use. Refer to 8.2.1.

Eye Contact:

Safety glasses with side shields or face shield are recommended to prevent eye contact.

Hand Contact:

Impervious gloves (nitrile or equivalent) should be worn to prevent hand contact.

Skin Contact:

Lab Coat or similar garment should be worn.

8.2.3 Environmental Controls: No special environmental controls are required.

SECTION 9 – Physical and Chemical Properties

Characteristic	Stop Solution #4978 Sulfuric Acid <10%
Boiling Point (°C)	Not available
Melting Point (°C)	Not available
Specific Gravity	1.07
Vapor Pressure (mm Hg) @ 25° C	Not available
Vapor Density (AIR = 1)	Not available
Evaporation Rate (Ether = 1)	Not available
pH:	≤1.0
Solubility in Water:	Miscible in water
Appearance and Odor:	Clear, odorless

SECTION 10 – Stability and Reactivity

Characteristic	Stop Solution #4978 Sulfuric Acid <10%
Stability	Stable under recommended storage conditions
Conditions to Avoid	Heat; Incompatible materials
Materials to avoid (Incompatibilities)	Strong oxidizing and reducing agents; potassium chlorate, potassium perchlorate, sodium, bases, organic material, metals (yields hydrogen gas), and many other reactive substances
Hazardous Decomposition or Byproducts	Thermal decomposition may release irritating fumes of oxides of sulfur
Hazardous Polymerization	None under normal processing

SECTION 11 – Toxicological Information

11.1 Toxicity Data for Hazardous Ingredients: There are currently no toxicity data available for the components of this specific kit; the following toxicology information is available for raw materials present in greater than 1% concentration.

The following data are available for **Sulfuric Acid (RTECS #WS5600000)**:

Skin and Eye Irritation: Eye/Rabbit 250 µg severe effect
Eye/Rabbit 5 mg/30S rinse severe effect

Reproductive Effects: Inhalation/Rabbit
Lowest published toxic concentration: 20-mg/m³/7 hour (6-18 day pregnant)
Effect: Reproductive: Specific developmental abnormalities: Musculoskeletal system

Acute Toxicity Data: Inhalation/Human
Lowest published toxic concentration: 3-mg/m³/24 hour
Effect: Musculoskeletal: Changes in the teeth and supporting structures
Inhalation/Mouse
LC50: 320 mg/m³/2 hour
Inhalation/Rat
LC50: 510 mg/m³/2 hour
Oral/Rat
LD50: 350 mg/kg
Unreported Route Man
Lowest published LD50: 135 mg/kg

11.2 Primary Routes of Exposure:

Overexposures to components within this kit are not expected. Common routes of exposure may include ingestion and eye/skin contact. Inhalation exposure possible with inadequate ventilation controls. Specific paths of concern for potentially infectious materials are skin puncture, contact with broken skin, contact with mucous membranes and inhalation of aerosolized material.

11.3 Potential Effects of Acute Overexposure, By Route Of Exposure:

This kit contains material of animal origin and should be considered as potentially capable of transmitting infectious diseases. Follow Universal Precautions.

INHALATION: Vapors, mists, sprays, or dusts of this kit can cause irritation to the respiratory tract.

CONTACT WITH SKIN or EYES: Contact can cause eye or skin irritation.

SKIN ABSORPTION: May be harmful if absorbed through skin.

INGESTION: If components within this kit are swallowed, irritation of the mouth, throat, and other tissues of the gastro-intestinal system may occur.

INJECTION: Accidental injection of chemical components within this kit can cause burning, reddening, and swelling in addition to the wound. Symptoms of such exposure can include those described under "Inhalation," "Contact with Skin or Eyes," and "Ingestion."

11.4 Potential Effects of Chronic Exposure:

Long-term skin or eye contact can result in dermatitis or eye irritation. Prolonged or repetitive exposure to Sulfuric Acid may increase risk of cumulative effects.

11.5 Symptoms of Overexposure:

Symptoms of overexposure to Sulfuric Acid may include: eye, skin, nose, and throat irritation, headache, nausea and vomiting, and burns to contacted areas. Contact with the eyes may lead to blurred vision, redness, pain, and burns to eye tissue. Symptoms may be delayed for several hours after exposure.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated for this specific kit.

11.6 Medical Exposure Aggravated by Exposure:

Persons with pre-existing skin disorders, eye problems or impaired respiratory system function can be more susceptible to health effects associated with overexposures to the components within this kit.

11.7 Carcinogenicity:

CHEMICAL NAME	ACGIH	IARC	NTP	OSHA
Sulfuric Acid	No	No	No	No

Cancer Status: *The International Agency for Research on Cancer (IARC) has classified "strong inorganic acid mists containing sulfuric acid" as a known human carcinogen (IARC Category 1). This classification applies only to mists containing sulfuric acid and NOT to sulfuric acid or sulfuric acid solutions.*

SECTION 12 – Ecological Information

12.1 Ecotoxicity – Not Available

No adverse effects on the environment are expected from the components of this kit. There is no aquatic toxicity data for this kit at this time. Individual aquatic toxicity studies have been completed for the below listed chemicals.

Sulfuric Acid

Bluegill/Sunfish:	49 mg/L / 48-hour	TLM (Tap water @ 20° C)
LC50 Flounder:	100 to 300 mg/L / 48-hour	Aerated water
LC50 Shrimp:	80 to 90 mg/L / 48-hour	Aerated water
LC50 Prawn:	42.5 ppm / 48-hour	Salt water

**This material may be toxic to aquatic wildlife

12.2 Mobility

Mobility data are not available for the components of this kit.

12.3 Persistence and Degradability

There is no persistence or degradation data for any component of this kit at this time.

12.4 Bioaccumulative Potential

There is limited potential for the components within this kit to accumulate in plant or animal systems.

SECTION 13 – Disposal Considerations

Dispose of waste materials, unused components and contaminated packaging in compliance with country (i.e., Canada, EU), federal, state and local regulations. If unsure of the applicable requirements, contact the authorities for information.

SECTION 14 – Transport Information

14.1 U.S. Transportation

This kit qualifies for the small quantity exception under 49 CFR 173.4 and is therefore not regulated per 49 CFR 172.101, the U.S. department of transportation.

Per 49 CFR 173.4, small quantities of Class 8 (corrosive) liquids not exceeding 30 ml per inner receptacle may be exempt from DOT requirements. Specific quantity, packaging and labeling requirements, as described in 49 CFR 173.4 (a), must be met to qualify for this exemption.

14.2 Canadian Transportation

The above-listed DOT basic description applies to this kit under the regulations of Transport Canada.

14.3 International Air Transportation

This kit qualifies as a “Dangerous Good in Excepted Quantity” under the provisions of Section 2.7 of the Dangerous Goods Regulations of the International Air Transportation Association (IATA).

Per Section 2.7 of the Dangerous Goods Regulations, very small quantities of dangerous goods may be exempted from marking, labeling and documentation requirements of the Dangerous Goods Regulations, as long as all the provisions of Section 2.7 are complied with.

SECTION 15 – Regulatory Information

This preparation is a component of an FDA-regulated in vitro diagnostic device.

15.1 U.S. Federal and State Regulations

	Stop Solution #4978 Sulfuric Acid <10%
40 CFR 355.30/355.40 - SECTION 302	Listed
40 CFR 302.4 – SECTION 304	RQ = 1000 lbs.
40 CFR 372.65 – SECTION 313	Listed for sulfuric acid aerosols only

U.S. SARA SECTION 311/312 FOR KIT:

Acute health effects; chronic health effects.

U.S. TSCA INVENTORY STATUS:

The components of this kit are listed on the TSCA Inventory.

OTHER U.S. FEDERAL REGULATIONS:

Not applicable.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):

Components within this kit are not found on either the Proposition 65 Carcinogen List or the Adverse Reproductive List.

15.2 Label Information

ANSI Z129.1	Stop Solution #4978 Sulfuric Acid <10%	Kit Package
Labeling:	CAUTION: May cause eye, skin and respiratory tract irritation.	CAUTION: Kit components may be harmful if swallowed, inhaled, or absorbed through skin. Components may be eye, skin and respiratory tract irritants.
Label Precautions:	Do not breathe mist. Do not swallow or take internally. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. Keep container closed. Use only with adequate ventilation.	Do not swallow or take internally. Do not get in eyes, on skin, or on clothing. This kit contains material of animal origin and should be considered as potentially capable of transmitting infectious diseases. Follow package insert instructions for use.

ENVIRONMENTAL HAZARDS:

Do not discharge effluent contained within this kit into streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this kit to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

15.3 Canadian Regulations:

CANADIAN DSL/NDL INVENTORY STATUS:

The components of this kit are listed on the DSL Inventory.

CANADIAN WHMIS SYMBOLS:

Stop Solution #4978 - Sulfuric Acid <10%



Class E


Corrosive Material

15.4 HMIS Ratings (See Page 10 for Definition of Ratings):

Stop Solution #4978 – Sulfuric Acid <10%

Health	2 *
Flammability	0
Physical Hazard	0
Protective Equipment	B

15.5 EU Labeling Classification:

<p>Classification: Stop Solution #4978 Sulfuric Acid <10%</p> <div style="text-align: center;">  </div> <p>Xi Irritant</p>	<p>Risk Phrases: R36/38 Irritating to eyes and skin</p> <p>Safety Phrases: S24/25 Avoid contact with skin and eyes S28 After contact with skin, wash immediately with plenty of water S36 Wear suitable protective clothing</p>
--	---

SECTION 16 – Other Information

PREPARED BY:	Quidel Corporation 10165 McKellar Court San Diego, CA 92121 1-800-874-1517
DATE OF PRINTING	March 28, 2007
<p>Quidel Corporation provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the materials contained in this kit by a properly trained person using this kit. Quidel Corporation shall not be held liable for any damage resulting from handling or use.</p>	



SC5b-9 PLUS ENZYME IMMUNOASSAY KIT (COMPLEMENT ASSAY KIT)



DEFINITIONS OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these, which are commonly used, include the following:

CAS #: This is the Chemical Abstract Service Number that uniquely identifies each compound.

ACGIH - American Conference of Governmental Industrial Hygienists, a professional association that establishes exposure limits.

TLV - Threshold Limit Value - an airborne concentration of a substance that represents conditions under which it is generally believed that nearly all workers can be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour Time Weighted Average (**TWA**), the 15-minute Short Term Exposure Limit, and the instantaneous Ceiling Level (**C**). Skin absorption effects must also be considered.

OSHA - U.S. Occupational Safety and Health Administration

PEL - Permissible Exposure Limit - This exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June, 1993 Air Contaminants Rule (Federal Register: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase, "Vacated 1989 PEL," is placed next to the PEL that was vacated by Court Order.

IDLH - Immediately Dangerous to Life and Health - This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury. **The DFG - MAK** is the Republic of Germany's Maximum Exposure Level, similar to the U.S. PEL.

NIOSH is the National Institute of Occupational Safety and Health, which is the research arm of the U.S. Occupational Safety and Health Administration (**OSHA**). NIOSH issues exposure guidelines called **Recommended Exposure Levels (RELs)**. When no exposure guidelines are established, an entry of **NE** is made for reference.

Protective Equipment - **A:** Safety Glasses. **B:** Safety glasses and gloves. **C:** Safety glasses, gloves and body protection. **D:** Splash goggles with face shield, gloves and body protection. **E:** Eye protection, gloves and dust mask respiratory protection. **F:** Eye protection, gloves, body protection and dust mask respiratory protection. **G:** Eye protection, gloves and air purifying respiratory protection.

HAZARD RATINGS:

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: Health Hazard: **0** (minimal acute or chronic exposure hazard); **1** (slight acute or chronic exposure hazard); **2** (moderate acute or significant chronic exposure hazard); **3** (severe acute exposure hazard; onetime overexposure can cause permanent injury and can be fatal); **4** (extreme acute exposure hazard; single overexposure can be fatal). * Indicates chronic hazard.

Flammability Hazard: **0** (minimal hazard); **1** (materials that require substantial pre-heating before burning); **2** (combustible liquid or solids; liquids with a flash point of 38-93°C [100-200°F]); **3** (Class IB and IC flammable liquids with flash points below 38°C [100°F]); **4** (Class IA flammable liquids with flash points below 23°C [73°F] and boiling points below 38°C [100°F]). Reactivity Hazard: **0** (normally stable); **1** (material that can become unstable at elevated temperatures or which can react slightly with water); **2** (materials that are unstable but do not detonate or which can react violently with water); **3** (materials that can detonate when initiated or which can react explosively with water); **4** (materials that can detonate at normal temperatures or pressures).

NATIONAL FIRE PROTECTION ASSOCIATION: Health Hazard: **0** (material that on exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials); **1** (materials that on exposure under fire conditions could cause irritation or minor residual injury); **2** (materials that on intense or continued exposure under fire conditions could cause temporary incapacitation or possible residual injury); **3** (materials that can on short exposure could cause serious temporary or residual injury); **4** (materials that under very short exposure could cause death or major residual injury). Flammability Hazard and Reactivity Hazard: Refer to definitions for "Hazardous Materials Identification System".

FLAMMABILITY LIMITS IN AIR: Much of the information related to fire and explosion is derived from the National Fire Protection Association (**NFPA**).

Flash Point - Minimum temperature at which a liquid gives off sufficient vapors to form an ignitable mixture with air. Autoignition Temperature: The minimum temperature required to initiate combustion in air with no other source of ignition. LEL - the lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source. UEL - the highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.

TOXICOLOGICAL INFORMATION:

Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. Definitions of some terms used in this section are: **LD₅₀** - Lethal Dose (solids & liquids) which kills 50% of the exposed animals; **LC₅₀** - Lethal Concentration (gases) which kills 50% of the exposed animals; **ppm** concentration expressed in parts of material per million parts of air or water; **mg/m³** concentration expressed in weight of substance per volume of air; **mg/kg** quantity of material, by weight, administered to a test subject, based on their body weight in kg. Other measures of toxicity include **TDLo**, the lowest dose to cause a symptom and **TCLo** the lowest concentration to cause a symptom; **TDo**, **LDLo**, **LDo**, **TC**, **TCo**, **LCLo**, and **LCo**, the lowest dose (or concentration) to cause lethal or toxic effects. **BEI** - Biological Exposure Indices, represent the levels of determinants that are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV. Ecological Information: **EC** is the effect concentration in water.

Data from several sources are used to evaluate the cancer-causing potential of the material. The sources and ratings are: **IARC** - the International Agency for Research on Cancer; 1 = Carcinogenic to humans, 2A, 2B = Probably carcinogenic to humans, 3 = Unclassifiable as to carcinogenicity in humans, and 4 = Probably not carcinogenic to humans. **NTP** - the National Toxicology Program; K = Known to be a human carcinogen, and R = Reasonably anticipated to be a human carcinogen. **RTECS** - the Registry of Toxic Effects of Chemical Substances. **OSHA** - Occupational Safety and Health Administration and **CAL/OSHA** - California's subunit of the Occupational Safety and Health Administration; Ca = Carcinogen defined with no further categorization. **ACGIH** - American Conference of Governmental Industrial Hygienists; A1 = Confirmed human carcinogen, A2 = Suspected human carcinogen, A3 = Confirmed animal carcinogen with unknown relevance to humans, A4 = Not classifiable as a human carcinogen, and A5 = Not suspected as a human carcinogen. **NIOSH** - U.S. National Institute for Occupational Safety and Health; Ca = Potential occupational carcinogen, with no further categorization. **EPA** - U.S. Environmental Protection Agency; A = Human carcinogen, B = Probable human carcinogen, C = Possible human carcinogen, D = Not classifiable as to human carcinogenicity, E = Evidence of Non-carcinogenicity for humans, K = Known human carcinogen, L = Likely to produce cancer in humans, CBD = Cannot be determined, NL = Not likely to be carcinogenic in humans, and I = Data are inadequate for an assessment of human carcinogenic potential.

REGULATORY INFORMATION:

This section explains the impact of various laws and regulations on the material. **EPA** is the U.S. Environmental Protection Agency. **WHMIS** is the Canadian Workplace Hazardous Materials Information System. **DOT** and **TC** are the U.S. Department of Transportation and the Transport Canada, respectively.

Superfund Amendments and Reauthorization Act (SARA); the Canadian Domestic/Non-Domestic Substances List (**DSL/NDL**); the U.S. Toxic Substance Control Act (**TSCA**); Marine Pollutant status according to the **DOT**; the Comprehensive Environmental Response, Compensation, and Liability Act (**CERCLA or Superfund**); and various state regulations. This section also includes information on the precautionary warnings that appear on a material's industrial package label.